

TEII - Residential Series

Tipton Environmental residential units, the TEII Residential Series, are manufactured in a number of convenient sizes - measured by gallons per minute (GPM) flow rates. These systems can be used in homes, boats, and recreational vehicles or in pools and spas. The units can be installed where water enters the residence (point of entry - POE) or under counters (point of use - POU).



The TEII - Residential units can be used alone or in conjunction with other systems such as carbon filtration, reverse osmosis or water softeners.

RESIDENTIAL SPECIFICATION CHART						
TEII - Residential Series						
UNIT	GPM	GPH	INLET/OUTLET	AMPS		NO. OF LAMPS
				120V	220V	
TEII-RS-3	3	180	3/8" NPT	0.42	0.21	1-15"
TEII-RS-7	7	420	3/4" NPT	0.42	0.21	1-17"
TEII-RS-15	15	900	3/4" NPT	0.42	0.21	1-36"
TEII-RS-30	30	1,800	1 1/2" NPT	1.3	0.65	2-36"
TEII-RS-50	50	3,000	2" NPT	2.1	1.1	4-36"

Standard Features:

- 304 stainless steel construction
- NPT fittings
- Electro-polished and passivated
- L.E.D. display to indicate lamp status on/off
- UV lamps with 9,000 hour life
- Pure fused quartz
- 30,000 $\mu\text{ws}/\text{cm}^2$
- Mounting brackets for vertical or horizontal installation

Optional Features:

- Carbon pre-filters
- Polypropylene housings
- Ultraviolet monitors
- Manual quartz cleaning systems
- Flow control
- Audible lamp out alarm



T I P T O N
E N V I R O N M E N T A L
 I n t e r n a t i o n a l , I n c .

4446 State Route 132 Batavia, OH 45103 USA
 Voice: 513.735.2777 Fax: 513.735.1485
 E-mail: info@tiptonenv.com
www.wastewaterdepot.com